




DRG-Window connection tape TWIN A-V

Technical Information

	<p>Product structure DRG-Window connection tape TWIN A-V is a flashing tape with moisture adaptive Sd value and with an aggressive adhesive for excellent adhesion even on construction sites, easy converting due to split release liner and high tensile strength in machine- and cross-direction, very good temperature resistance, free of emulsifiers and APEOs, solvent free adhesive with very low emissions and excellent ageing resistance, outdoor exposure up to 3 months, can be plastered.</p> <p>Applications Indoor and outdoor sealing of window frames and frontwall installations in damp locations.</p>
---	--

Technical Information – Product characteristic

Carrier	--	Special-PET/PA non-woven film, white
Adhesive	--	UV acrylic
Liner	--	Siliconized PP film
Thickness	DIN EN 1942	0.4 mm
Elongation at break	DIN EN 14410	25 %
Tensile strength, md	DIN EN 14410	40 N/cm
Tensile strength, cd	DIN EN 14410	40 N/cm
Adhesion to steel	DIN EN 1939	15 N/cm
Temperature range	--	-40 to +100 °C
Processing	--	> 5 °C

**STORAGE: AT ABOUT 5 °C TO 35 °C AND DRY IN ORIGINAL PACKING;
12 MONATE NACH EINGANG BEIM KUNDEN HALTBAR.**